

## Claims

1. An organic electroluminescent display comprising: an organic electroluminescent device, and a color converting member comprising a shielding layer and a shielding layer aperture region including a color converting layer, edges of the aperture region being closer to the center of the aperture region than edges of an emission region of the organic electroluminescent device.
- 10
2. The organic electroluminescent display according to claim 1, wherein a perpendicular distance  $h$  ( $\mu\text{m}$ ) from the shielding layer to an emitting layer of the organic electroluminescent device and a length  $X$  ( $\mu\text{m}$ ) of an overlapping part of the shielding layer and the emission region satisfy the following expression (I).
- 15
- $$X/h \geq 0.60 \quad (I)$$
3. The organic electroluminescent display according to claim 1, wherein the area of the shielding layer aperture region is 70% or more of the area of the organic electroluminescent emission region.
- 20
4. The organic electroluminescent display according to claim 1, further comprising a reflection preventing part on the side of the color converting member from which light from the organic electroluminescent device is outcoupled.
- 25
5. The organic electroluminescent display according to claim 4, wherein the reflection preventing part is a
- 30

reflection preventing film.

6. The organic electroluminescent display according to  
claim 4, wherein the reflection preventing part is a non-  
5 glare film.

7. The organic electroluminescent display according to  
claim 1, further comprising a transparent medium layer  
between the organic electroluminescent device and the color  
10 converting member.

8. The organic electroluminescent display according to any  
one of claims 1 to 7 which is actively driven.